

Parameter

Item	Unit	XG0607DC	XG0608DC	XG0708DC
Dimension				
Max. working height	m	5.9	6.6	7.7
Max. platform height	m	3.9	4.6	5.7
Overall length a	mm	1450	1558	1558
Overall length (without ladder)	mm	1290	1390	1390
Overall width b	mm	760	810	810
Overall height c	mm	2020	2020	2120
Overall height (platform folded)	mm	1660	1660	1760
Platform dimension (length d * Width e)	mm	1290 × 700	1370 × 700	1370 × 700
Extended platform dimension	mm	600	600	600
Min. ground clearance (elevated/stowed state)	mm	15 / 65	24 / 65	24 / 58
Tire	mm	254 × 76	254 × 76	254 × 76
Wheelbase f	mm	1030	1130	1130
Performance				
Max. number of occupants	/	2	2	2
Work platform rated load	kg	240	240	240
Extension platform rated load	kg	100	120	120
Travel speed (lowered/elevated position)	km/h	4 / 0.5	4.0 / 0.5	4 / 0.5
Min. turning radius (inside/outside wheel)	m	0.4 / 1.55	0.45 / 1.6	0.45 / 1.6
Work platform raising/lowering time	s	27-37 / 23-33	28-38 / 24-34	28-40 / 24-36
Max. gradeability	%	25	25	25
Tilt alarm angle (sideways/forward or back)	°	1.5 / 3	1.5 / 3	1.5 / 3
Total weight	kg	900	900	1200
Power source				
Battery	/	Maintenance free lead-acid battery	Maintenance free lead-acid battery	Maintenance free lead-acid battery
Battery capacity	AH	85	85	115
Options		AC power to the platform Air-line to platform Platform working light Weighing overload alarm		

