

Parameter

Item	Unit	XG0807HD-li	XG0807HA-li	XG0807HDW-li	XG0807HAW-li
Dimension					
Max. working height	m	7.8	7.8	7.8	7.8
Max. platform height	m	5.8	5.8	5.8	5.8
Overall length a	mm	1900	1900	1900	1900
Overall length (without ladder)	mm	1680	1680	1680	1680
Overall width b	mm	760	760	810	810
Overall height c	mm	2160	2160	2160	2160
Overall height (platform folded)	mm	1830	1830	1830	1830
Platform dimension (length d * Width e)	mm	1670 × 740	1670 × 740	1670 × 740	1670 × 740
Extended platform dimension	mm	900	900	900	900
Min. ground clearance (elevated/stowed state)	mm	20 / 71	20 / 71	20 / 71	20 / 71
Tire	mm	323 × 100	323 × 100	323 × 100	323 × 100
Wheelbase f	mm	1360	1360	1360	1360
Performance					
Max. number of occupants	/	2	2	2	2
Work platform rated load	kg	230	230	230	230
Extension platform rated load	kg	115	115	115	115
Travel speed (lowered/elevated position)	km/h	3 / 0.8	3 / 0.8	3 / 0.8	3 / 0.8
Min. turning radius (inside/outside wheel)	m	0 / 1.75	0 / 1.75	0 / 1.75	0 / 1.75
Work platform raising/lowering time	s	15-25 / 25-35	15-25 / 25-35	15-25 / 25-35	15-25 / 25-35
Max. gradeability	%	25	25	25	25
Tilt alarm angle (sideways/forward or back)	°	1.5 / 3	1.5 / 3	1.5 / 3	1.5 / 3
Total weight	kg	1550	1550	1580	1580
Power source					
Battery	/	Lithium battery			
Battery capacity	AH	150			
Options		AC power to the platform Air-line to platform Platform working light Weighing overload alarm			

