

Parameter

Item	Unit	XG1008HD-li/XG1008HA-li	XG1012HD-li/XG1012HA-li
Dimension			
Max. working height	m	10	10
Max. platform height	m	8	8
Overall length a	mm	2477	2477
Overall length (without ladder)	mm	2280	2267
Overall width b	mm	810	1170
Overall height c	mm	2335	2335
Overall height (platform folded)	mm	2005	1805
Platform dimension (length d * Width e)	mm	2280 × 810	2280 × 1120
Extended platform dimension	mm	900	900
Min. ground clearance (elevated/stowed state)	mm	20 / 100	20 / 110
Tire	mm	381 × 127	381 × 127
Wheelbase f	mm	1877	1877
Performance			
Max. number of occupants	/	2	2
Work platform rated load	kg	230	450
Extension platform rated load	kg	115	115
Travel speed (lowered/elevated position)	km/h	3.5 / 0.8	3.5 / 0.8
Min. turning radius (inside/outside wheel)	m	0 / 2.3	0 / 2.3
Work platform raising/lowering time	s	29-40 / 34-45	29-40 / 49-60
Max. gradeability	%	25	25
Tilt alarm angle (sideways/forward or back)	°	1.5 / 3	1.5 / 3
Total weight	kg	2260	2680
Power source			
Battery	/	Lithium battery	Lithium battery
Battery capacity	AH	173	202
Options		AC power to the platform Air-line to platform Platform working light Weighing overload alarm	

