



Parameter


Item	Unit	XGS22K
Dimension		
a. Overall length (stowed)	mm	10080
Overall length (transportation)	mm	9850
b. Overall width	mm	2490
c. Overall height	mm	2530
Platform dimension	mm	2440 × 900 × 1150
d. Wheelbase	mm	2500
Max. working height	mm	22000
Max. platform height	mm	20000
Max. working range	mm	17200
Performance		
Max. load capacity	kg	300 (Unrestricted) / 460 (Restricted)
Walking speed (stowed)	km/h	6.3
Walking speed (elevated/extended)	km/h	0.6
Boom luffing range	°	-3~ 73
Rotation angle of turntable	°	360 continuous
Tailswing	mm	1310
Rotation angle of platform	°	160
Min. turning radius (outside)	mm	6000
Min. turning radius (inside)	mm	3280
Overall weight	kg	12460
Max. gradeability (counterweight upwards)	%	45
Max. gradeability (counterweight downwards)	%	30
Power source		
Engine model	/	Yuchai YCF3050-T302/Kubota V2403-M-DI-E3B/Yuchai YCF3050-T423
Rated power	kW	36.8 / 36 / 36.8
Hydraulic tank capacity	L	120
Hydraulic system capacity	L	240
Fuel tank capacity	L	150

Options

Anti extrusion device / Tool tray / Working light / Anti-squeeze hand-assisted track of the platform
Half-height mesh platform / Aircraft protection device / Anti-falling assembly



Work Curve Graph



Global service hotline: 400 110 9999

